

Appln No. 09/363,121  
Amdt date October 20, 2003  
Reply to Office action of August 12, 2003

OK  
to enter  
DW  
10/28/03

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A cathode ray tube comprising:  
a panel having a phosphor screen;  
a cylindrical neck having an electron gun assembly disposed therein for generating a plurality of electron beams;  
a funnel formed between the panel and the neck, and having a substantially rectangular cone portion contiguous to the neck, the substantially rectangular cone portion having rounded inside corners tangentially joining adjacent cone walls of the rectangular cone portion;  
an anode button on the funnel to supply a voltage in the funnel; and  
an inner graphite layer disposed on an inner surface of the funnel to form a path for transmission of the voltage,  
wherein the inner graphite layer satisfies the following condition:

$T_d / T_h$  is within the ranges of either  $0.9 \leq T_d / T_h < 1$   
[and] or  $1 < T_d / T_h \leq 1.36$

where  $T_d$  is an approximate thickness of the inner graphite layer along each rounded inside corner tangentially joining adjacent cone walls of the rectangular cone portion, and  $T_h$  is

Appln No. 09/363,121

Amdt date October 20, 2003

Reply to Office action of August 12, 2003

an approximate thickness of the inner graphite layer disposed on inside horizontal walls of the cone portion.

2. (Currently Amended) A cathode ray tube comprising:

a panel having a phosphor screen;

a cylindrical neck having an electron gun assembly disposed therein for generating a plurality of electron beams;

a funnel formed between the panel and the neck, and having a substantially rectangular cone portion contiguous to the neck, the substantially rectangular cone portion having rounded inside corners tangentially joining adjacent cone walls of the rectangular cone portion;

an anode button on the funnel to supply a voltage in the funnel; and

an inner graphite layer disposed on an inner surface of the funnel to form a path for transmission of the voltage,

wherein the inner graphite layer satisfies the following condition:

Td / Tv is within the ranges of either  $0.9 \leq Td / Tv < 1$   
[[and]] or  $1 < Td / Tv \leq 1.36$

where Td is an approximate thickness of the inner graphite layer along each rounded inside corner tangentially joining adjacent cone walls of the rectangular cone portion, and Tv is an approximate thickness of the inner graphite layer disposed on inside vertical walls of the cone portion.